



Fall protection

AN213100ZDD

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high-impact webbing, for short distances



Specific benefits



Hygiene

· Can wash harnesses and textiles with neutral soap



Performance

· Certification above maximum rated load 100kg; product certified at 140kg
· Webbing with better abrasion resistance and certified against sharp edges

Applications

- Public Works
- Finishing Works/Craftsmanship
- Automotive
- Power Energy
- Storage

Certifications and norms



EN355

HORIZONTAL CERTIFICATION
RFU 11.062
140 KG



Fall protection

AN213100ZDD

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high-impact webbing, for short distances

Standards - Details

Technical details

| | |
|---------------------------------|--|
| Type of equipment | Energy absorber in lanyard webbing |
| Composition of the main support | Steel, Polyester |
| Length | 1 m |
| With connector | yes |
| Color | Orange |
| Connector 1 | Screw carabiner, steel, opening 18mm |
| Ending | 2 sewn thimble loops |
| Connectors (structure side) | 2 automatic lock hooks, steel, opening 55mm |
| Lifespan from manufacturing | 10 years |
| Weight | 1,3 kg |
| Fall arrest work situations | Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m), Long movement with multi connection /disconnection |



Fall protection

AN213100ZDD

ENERGY ABSORBING LANYARDS

Double energy absorbing lanyard, made of high-impact webbing, for short distances

Logistics Information

| Reference | Color | Size | Designation | EAN13 | Box Code | Multiple Sales | Minimum Order Quantity | Weight |
|-------------|--------|------|-------------|---------------|----------------|----------------|------------------------|---------|
| AN213100ZDD | Orange | 1 m | AN213100ZDD | 3295249265076 | 13295249265073 | 5 | 1 | 8.58 kg |